

MORA COAT 700

MORA COAT 700 is a high-quality semi- gloss latex paint for interior and exterior use.

General Specifications:

It is a bright white semi-gloss latex paint, based on concentrated acrylic and vinyl acetate co-polymer emulsions, together with a high percentage of high-quality titanium dioxide.



Uses:

- ✚ Semi-gloss paint for cement plastering, concrete, masonry, asbestos, wood and other surfaces.
- ✚ It can be applied on gypsum surfaces, after first applying a primer coat of Morabond65 diluted with water (ratio 1:3).

Technical Characteristics: (at 25 ° C):

Color:	White & Colored
Density (kg/lt.):	1.27 ± 0.02
Viscosity:	134 ± 1 KU
Consumption Rate:	8 – 10 m ² / kg / coat

How to Use:

- ✚ Surfaces should be cleaned well from dust, oils, etc.
- ✚ Porous surfaces should be primed with a sealer coat of MORACOAT100 diluted with water (ratio 1:1).
- ✚ Cavities should be filled and surfaces must be smoothed using one or more coats of MORACOAT 400 Fine PUTTY.
- ✚ Apply an undercoat of MORACOAT 400.
- ✚ Stir MORA COATE 700 well before use.
- ✚ Apply one or more coats of MORA COATE 700 according to surface condition using a brush, roller or-spray gun.
- ✚ In case of spraying, dilute MORACOAT 400 with 5 - 10 % water for ease of application.

N.B:

To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage: 12 months under proper storing conditions.



Packs: 20KG.